

SHORT STUFF®

Suggested Starting Formulation

ELASTOMERIC ROOF MASTIC CONTAINING SHORT STUFF® HDPE E505F

MATERIALS:

	<u>% by weight</u>
Water	12.00
MiniFIBERS' SHORT STUFF® HDPE E505F	2.00
Natrosol - 250MR	1.00
Tamol 850.....	0.40
KTPP.....	0.10
Ethylene Glycol.....	2.00
Nopco NXZ.....	0.15
TiO ₂ - R-960.....	6.00
Duramite®.....	34.50
Kadox 515.....	4.00

Grind for 15 minutes at high speed, then let down with the following:

Emulsion E-1685.....	35.50
Texanol.....	1.00
Skane M8.....	0.16
Nopco NXZ.....	0.15
NH ₄ OH.....	0.07
Water.....	1.00
	<u>100.03</u>

Mix for 15 minutes to a smooth consistency.

PHYSICAL PROPERTIES:

Weight per Gallon..... 12.28 lbs.

Viscosity..... 140+ Ku

Application..... Squeegee, trowel, brush, and airless spray.

- 1) Excellent resistance to dirt pickup.
- 2) Excellent adhesion to a variety of substrates (wood, urethane foam, galvanized steel, asphalt, etc.)

MINIFIBERS, INC.